




BACHMANN GmbH
VERBINDUNGSTECHNIK

Zollerstrasse 6-10
72379 Hechingen Germany
Telephone: +49 (0)7471 984580
Fax: +49 (0)7471 9845817
Email: info@bachmanngmbh.de
www.bachmanngmbh.de



BACHMANN GmbH
VERBINDUNGSTECHNIK



Ironing presses



Slide table-surface lamination-ironing press

- with two overlapping feed tables.
- The pressing time can be adapted to the removal and production times, which means laminating that's gentle to materials (little shrinkage, and maintenance of the grain structure). With integrated activation plate to fix Thermal -coated small parts (toe caps, strengthening components) before lamination.
- Removable clamping frame covered with silicone separating film. This allows parts that are stuck together in the press to be removed quickly.
- Electropneumatic controls for time and pressure and electronic temperature regulation with digital display ensure a constant laminating result. A hydraulic height adjustment and mobile frame is available as an option.

Technical data:

Dimensions:

Space needed	approx. 3700 (2200 without storage)/ 2180/ 1250 mm
Weight	approx. 850 kg

Pneumatics:

Operating pressure	max. 6 bar
Pressing force	28 KN
Air consumption	approx. 120l per double stroke (6bar)

Electrical information:

Connected load	400V/ 50 Hz, 3-ph, 21 A (min. 5x4i2)
Power consumption	calc. 10.1 KW
Temperature area	20-200 °C
Pressing time	0-10 h
Cooling time	3-60 sec.

Deliverable in various dimensions

