



#### T 30 Table dispenser

Suitable for film tapes up to 20 mm wide, with a special blade for smooth, serration-free cuts and integrated finger guard. Including a roll holder for 24 mm (1") and 76 mm (3") roll cores.

##### Technical data:

##### Dimensions:

Depth 175 mm, width 75 mm, height 100 mm  
Weight: 1.1kg



#### A 900.6 rechargeable batteries

Tape length is programmable in millimetre increments. 6 different lengths can be stored. The preset lengths can be selected with the "select" key, or dispensed (processed) consecutively through the automatic cycle. In addition, the quantity of the lengths to be dispensed can be programmed.

##### Technical data:

- Length adjustment	keypad
- Memory	6 tape lengths can be stored
- Special feature	sequential work is possible
- Anti-static housing	yes
- Strip width	min 8 mm max 60 mm
- Tape length	min 5 mm max 999 mm
- Roll diameter	max 300 mm

##### Power supply:

- 24V DC 3,3 AH
- AC 100V, 120V, 220-240V/41W

##### Dimensions:

Depth 250 mm, width 250 mm, height 230 mm  
Weight: 5.6 kg



#### A 500

Handy, compact tape dispenser for efficient processing of self-adhesive tapes on a film or a paper basis (crepe) up to 25 mm wide - with automatic feed of the set lengths. Length adjustments S = 30 mm, M = 45 mm and L = 90 mm. The tape is torn using a serrated blade, triggering the next dispensing procedure.

Ideal for office and packaging, inexpensive, simple and safe to use.  
Operated by power supply unit or battery.

##### Technical data:

Electrical connection voltage  
230V / 4.5V - 50Hz, 1 - ph  
Power consumption 0.01kw

##### Dimensions:

Depth 97mm, width 175mm, height 117mm  
Weight: 1.0kg without rechargeable batteries



#### A 501

Handy, compact tape dispenser for efficient processing of self-adhesive tapes on a film or a paper basis (crepe) up to 25 mm wide - with automatic feed of the set lengths. The tape lengths are programmable in 5 mm increments from 30 to 95 mm.


Ideal for office and packaging, inexpensive, simple and safe to use.  
Operated by power supply unit or battery.

##### Technical data:

Electrical connection voltage  
230V / 4.5V - 50Hz, 1 - ph  
Power consumption 0.01kw


##### Dimensions:

Depth 97mm, width 175mm, height 117mm  
Weight: 1.0kg without rechargeable batteries



**BACHMANN** GmbH  
VERBINDUNGSTECHNIK

Zollerstrasse 6-10  
72379 Hechingen Germany  
Telephone: +49 (0)7471 984580  
Fax: +49 (0)7471 9845817  
Email: [info@bachmanngmbh.de](mailto:info@bachmanngmbh.de)  
[www.bachmanngmbh.de](http://www.bachmanngmbh.de)



**BACHMANN** GmbH  
VERBINDUNGSTECHNIK





**A 690N, A 691N**

The tape length is programmable with five memory locations in millimetre increments.  
The device is equipped with a photoelectric cutting device as standard.  
The device A691N is suited for narrow tapes.

**Technical data:**

Length adjustment	keypad
Tape width	min. 9 mm / 5 mm max. 50 mm
Tape length	min. 5 mm, max. 999 mm
Roll diameter	160 mm

**Dimensions:**

Depth 210 mm, width 135 mm, height 150 mm  
Weight: 2.7 kg



**A695, A696, A697, A698**

Tape length is programmable in millimetre increments.  
The device is equipped with a photoelectric cutting device as standard.  
Device A695 has 1 memory location.  
Device A697 has 3 programmable lengths.  
The device A696/A698 is suited for narrow tapes.

**Technical data:**

Length adjustment	keypad
Tape width	min. 9 mm / 5 mm max. 50 mm
Tape length	min. 30mm max. 999mm *optional from 5mm
Roll diameter	160 mm

**Dimensions:**

Depth 210 mm, width 135 mm, height 150 mm  
Weight: 2.7 kg



**A900.6**

Tape length is programmable in millimetre increments.  
6 different lengths can be stored.  
The preset lengths can be selected with the "select" key, or dispensed (processed) consecutively through the automatic cycle.  
In addition, the quantity of the lengths to be dispensed can be programmed.

**Technical data:**

- Length adjustment	keypad
- Memory	6 tape lengths can be stored.
- Special feature	sequential work is possible
- Anti-static housing	yes
- Tape width	min. 6 mm max. 60 mm
- Tape length	min. 5 mm max. 999 mm
- Roll diameter	max 300 mm

**Dimensions:**

Depth 213 mm, width 116 mm, height 140 mm  
Weight: 1.8kg



**A900.6C**

Tape length is programmable in millimetre increments.  
6 different lengths can be stored.  
The preset lengths can be selected with the "select" key, or dispensed (processed) consecutively through the automatic cycle.  
In addition, the quantity of the lengths to be dispensed can be programmed.  
With motor cooling.

**Technical data:**

- Length adjustment	keypad
- Memory	6 tape lengths can be stored.
- Special feature	sequential work is possible
- Anti-static housing	yes
- Tape width	min. 6 mm max. 60 mm
- Tape length	min. 5 mm max. 999 mm
- Roll diameter	max 300 mm

**Dimensions:**

Depth 213mm, width 160mm, height 140mm  
Weight: 1.9kg



**A900.6F**

In addition to the functions of the A900.6, the device can fold a non-adhesive drag point of 7mm next to the beginning of the tape.  
Tape length is programmable in millimetre increments.  
6 different lengths can be stored.  
The preset lengths can be selected with the "select" key, or dispensed (processed) consecutively through the automatic cycle. In addition, the quantity of the lengths to be dispensed can be programmed.

**Technical data:**

- Length adjustment	keypad
- Memory	6 tape lengths can be stored
- Special feature	sequential work is possible
- Tape width	min. 6 mm max. 60 mm
- Tape length	min. 5 mm - 999 mm without folding function min. 15 mm - 999 mm with folding function
- Roll diameter	max 300 mm

**Dimensions:**

Depth 225mm, width 116mm, height 150mm  
Weight: 2.0kg



**A900.12**

Tape length is programmable in millimetre increments.  
It can be programmed with up to 12 different lengths.  
The preset lengths can be selected with the "select" key, or dispensed (processed) consecutively through the automatic cycle.  
In addition, the quantity of the lengths to be dispensed can be programmed.

**Technical data:**

- Length adjustment	keypad
- Memory	12 tape lengths can be stored
- Special feature	sequential work is possible
- Tape width	min. 6 mm max. 60 mm
- Tape length	min. 5 mm max. 999 mm
- Roll diameter	max 300 mm

**Dimensions:**

Depth 213mm, width 116mm, height 140mm  
Weight: 1.8kg