

A 521.60 rechargeable batteries

All common and special self-adhesive labels can be dispensed quickly and easily with the A521.60 rechargeable batteries label dispenser. Scanning is photoelectric. Dispensing rates and label feed rates are continuously adjustable. The built-in counter indicates how many labels you have already removed.

Technical data:


- Labels of 20-60 mm width,
- Photoelectric scanning
- Stock roll carrier for rolls of up to 210 mm outer diameter
- Cut-off speed and label speed can be regulated
- Counting function
- Digital display
- Powered by rechargeable batteries

Power supply:

- 12V DC 3,0AH
- AC 100V, 120V, 220-240V/41W Parameters can be managed simply using 100 internally stored programs.


Dimensions:

Depth: 230 mm, width: 250 mm, height: 180 mm



BACHMANN GmbH
VERBINDUNGSTECHNIK

Zollerstrasse 6-10
72379 Hechingen Germany
Telephone: +49 (0)7471 984580
Fax: +49 (0)7471 9845817
Email: info@bachmanngmbh.de
www.bachmanngmbh.de



BACHMANN GmbH
VERBINDUNGSTECHNIK



Label dispensers



A 524.60

All common and special self-adhesive labels can be dispensed quickly and easily with the label dispenser A524.60. Scanning is photoelectric. Dispensing speed and label feed rate are controllable in six levels from 50 to 100, in increments of ten. The built-in counter indicates how many labels you have already removed.

Technical data:

- Label dispenser for labels of 15-60 mm width
- Length 10 to 999 mm
- 6 different setting modes:
 - Auto / Manual
 - Counting function
 - Label recognition
 - Speed control
- Dispensing speed 100 to 200 mm/sec (six levels can be programmed)
- Roll mounting up to a 200 mm diameter, with adjustable roll holders on the sides
- Rewinding reel for carrier paper.

Dimensions:

Depth: 230 mm, width: 120 mm, height: 150 mm



A 524.120

All common and special self-adhesive labels can be dispensed quickly and easily with the label dispenser A524.120. Scanning is photoelectric. Dispensing speed and label feed rate are controllable in six levels from 50 to 100, in increments of ten. The built-in counter indicates how many labels you have already removed.

Technical data:

- Label dispenser for labels of 15-120 mm width
- Length 10 to 999 mm
- 6 different setting modes:
 - Auto / Manual
 - Counting function
 - Label recognition
 - Speed control
- Dispensing speed 100 to 200 mm/sec (six levels can be programmed)
- Roll mounting up to a 200 mm diameter, with adjustable roll holders on the sides
- Rewinding reel for carrier paper.

Dimensions:

Depth: 230 mm, width: 180 mm, height: 150 mm



A 524.180

All common and special self-adhesive labels can be dispensed quickly and easily with the label dispenser A524.180. Scanning is photoelectric. Dispensing speed and label feed rate are controllable in six levels from 50 to 100, in increments of ten. The built-in counter indicates how many labels you have already removed.

Technical data:

- Label dispenser for labels of 15-180 mm width
- Length 10 to 999 mm
- 6 different setting modes:
 - Auto / Manual
 - Counting function
 - Label recognition
 - Speed control
- Dispensing speed 100 to 200 mm/sec (six levels can be programmed)
- Roll mounting up to a 200 mm diameter, with adjustable roll holders on the sides
- Rewinding reel for carrier paper.

Dimensions:

Depth: 250 mm, width: 235 mm, height: 160 mm