

A 521.60 rechargeable batteries

With the label dispenser A521.60 rechargeable batteries, all current and special self-adhesive labels can be dispensed quickly and easily. Scanning is photoelectric. The dispensing speed and label feed rate are continuously adjustable. The built-in counter indicates how many labels you have already removed.

Technical data:

- Labels of 20-60 mm width,
- Photoelectric scanning
- Stock roll carrier for rolls of up to 210 mm outer diameter
- Cut-off speed and label speed can be regulated
- Counting function
- Digital display
- Powered by rechargeable batteries

Power supply:

12V DC 3.0AH
220-240V/41W

Dimensions:

Depth: 230 mm, width: 250 mm, height: 180 mm for sixties
Weight: 4.0 kg

A521.120/60-DIG

All current and special self-adhesive labels can be dispensed quickly and easily with the label dispenser A521.120/60. Two dispensers that work independently of each other are integrated into one device. Scanning is photoelectric. The dispensing and label feed rate are separately and continuously adjustable. The built-in meters each indicate how many labels you have already removed per work unit.

Technical data:


- Left unit: Labels of 20-120 mm width,
- Right unit: Labels of 20-60 mm width
- Photoelectric scanning
- Stock roll carrier for rolls of up to 210 mm outer diameter
- Cut-off speed and label speed can be regulated,
- Per work unit counting function
- Digital display

Power supply:

External power supply unit
100-240V, 50/60HZ


Dimensions:

Depth: 220 mm, width: 320 mm, height: 180 mm
Weight: 5.1 kg



BACHMANN GmbH
VERBINDUNGSTECHNIK

Zollerstrasse 6-10
72379 Hechingen Germany
Telephone: +49 (0)7471 984580
Fax: +49 (0)7471 9845817
Email: info@bachmanngmbh.de
www.bachmanngmbh.de



BACHMANN GmbH
VERBINDUNGSTECHNIK





A 521.60-DIG

All common and special self-adhesive labels can be dispensed quickly and easily with the label dispenser A521.60. Scanning is photoelectric. Dispensing rates and label feed rates are continuously adjustable. The built-in counter indicates how many labels you have already removed.

Technical data:

- Labels of 20-60 mm width,
- Photoelectric scanning
- Stock roll carrier for rolls of up to 210 mm outer diameter
- Cut-off speed and label speed can be regulated,
- Counting function
- Digital display

External power supply unit:

100-240V, 50/60HZ

Dimensions:

Depth: 220 mm, width: 125 mm, height: 175 mm
Weight: 2.8 kg



A521.120-DIG

All common and special self-adhesive labels can be dispensed quickly and easily with the label dispenser A521.120. Scanning is photoelectric. Dispensing rates and label feed rates are continuously adjustable. The built-in counter indicates how many labels you have already removed.

Technical data:

- Labels of 20-120 mm width,
- Photoelectric scanning
- Stock roll carrier for rolls of up to 210 mm outer diameter
- Cut-off speed and label speed can be regulated,
- Counting function
- Digital display

External power supply unit:

100-240V, 50/60HZ

Dimensions:

Depth: 220 mm, width: 200 mm, height: 175 mm
Weight: 3.2 kg



A 521.180-DIG

All common and special self-adhesive labels can be dispensed quickly and easily with the label dispenser A521.180. Scanning is photoelectric. Dispensing rates and label feed rates are continuously adjustable. The built-in counter indicates how many labels you have already removed.

Technical data:

- Labels of 20-180 mm width,
- Photoelectric scanning
- Stock roll carrier for rolls of up to 210 mm outer diameter
- Cut-off speed and label speed can be regulated,
- Counting function
- Digital display

External power supply unit:

100-240V, 50/60HZ

Dimensions:

Depth: 260 mm, width: 280 mm, height: 220 mm
Weight: 4.8 kg



A 521.300-DIG

All common and special self-adhesive labels can be dispensed quickly and easily with the label dispenser A521.300. Scanning is photoelectric. Dispensing rates and label feed rates are continuously adjustable. The built-in counter indicates how many labels you have already removed.

Technical data:

- Labels of 20-300 mm width
- Photoelectric scanning
- Stock roll carrier for rolls of up to 210 mm outer diameter
- Cut-off speed and label speed can be regulated,
- Counting function
- Digital display

External power supply unit:

100-240V, 50/60HZ

Dimensions:

Depth: 480 mm, width: 430 mm, height: 350 mm
Weight: 14.5 kg